



◆ SPECIFICATIONS

Current rating: 9A(2P AWG#16) AC, DC
 Voltage rating: 600V AC, DC
 Temperature range: -25°C ~ +85°C
 Insulation resistance: 1000MΩ Min.
 Withstanding voltage: 1500V AC/ minute.
 Contact resistance: 10mΩ Max.

Material: Nylon 66 UL 94V-2
 Circuits: 2~6P
 Suitable: KR4200 series female terminal
 Mates with KR4200 series single row female housing or wafer
 MOQ: 1,000PCS

PART NO.	Dimension	
	A	B
A4200N00213P60	4.20	9.60
A4200N00313P60	8.40	13.80
A4200N00413P60	12.60	18.00
A4200N00513P60	16.80	22.20
A4200N00613P60	21.00	26.40

F	④				GENERAL TOLERANCE	UNIT: mm	DATE	TITLE: MX 4.2 Single Row Female Housing			 东莞市康瑞电子有限公司 Dongguan Konnra Electronics co., LTD.			
	③				.X±0.30	X°±1°	DRAWN: 闵昕皓					2014.08.26		
	②				.XX±0.20	.X°±	CHECKED:		VER.	SCALE:	N/A	PROJECT	PART NO.	A4200N***13P60
	①				.XXX±0.10	.XX°±	APPROVED:		A	SHEET:	1/1	 DRAWING NO.	4200HF01-1-S	
	LTR	NAME	DATE	VERISION RECORD										
	1				2									
					3									
					4									
					5									
					6									
					7									
					8									
					9									