

◆SPECIFICATIONS

Current rating: 9A(2P AWG#16) AC, DC
 Voltage rating:600V AC,DC
 Temperature range: -25°C ~ +85°C
 Insulation resistance: 1000MΩ Min.
 Withstanding voltage: 1500V AC/ minute.
 Contact resistance: 10mΩ Max.


Material: Nylon 66 UL 94V-2
 Circuits: 2-6P
 Suitable: KR4200 series female terminal
 Mates with KR4200 series single row female housing or wafer

PART NO.	Dimension	
	A	B Δ
A4200K00213P60	4.20	11.70
A4200K00313P60	8.40	15.90
A4200K00413P60	12.60	20.10
A4200K00513P60	16.80	24.30
A4200K00613P60	21.00	28.50

Δ 4			
Δ 3			
Δ 2			
Δ 1	闵昕皓	2016.7.15	更正尺寸及"B"对照
LTR	NAME	DATE	VERISION RECORD

GENERAL TOLERANCE		UNIT: mm		DATE	
.X±0.30	X°±1°	DRAWN:	闵昕皓	2016.07.15	
.XX±0.20	.X°±	CHECKED:			
.XXX±0.10	.XX°±	APPROVED:			

TITLE: MK 4.2 Single Row Female Housing		
VER.	SCALE:	N/A
A1	SHEET:	1/1


东莞市康瑞电子有限公司
 Dongguan Konnra Electronics co., LTD.

PROJECT	PART NO.	A4200K***13P60
DRAWING NO.		4200HF02-1-S