


◆ SPECIFICATIONS

- Current rating: 5A AC, DC
- Voltage rating: 250V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 1500V AC/ minute.
- Contact resistance: 10mΩ Max.

Material: Nylon66 UL94 V-2
 Suitable: KR300HM series Terminal
 Mates With KR300HF Series Single Row Housing
 And KR300WF Series Single Row Wafer
 MOQ: 1,000PCS

PART NO.	Dimension	
	A	B
A3000N00240P60	3.0	7.00
A3000N00340P60	6.0	10.00
A3000N00440P60	9.0	13.00
A3000N00540P60	12.0	16.00
A3000N00640P60	15.0	19.00
A3000N00740P60	18.0	22.00
A3000N00840P60	21.0	25.00
A3000N00940P60	24.0	28.00
A3000N01040P60	27.0	31.00
A3000N01140P60	30.0	34.00
A3000N01240P60	33.0	37.00

F	△				GENERAL TOLERANCE	UNIT: mm	DATE	TITLE: MX 3.0 Single Row Female Housing			 东莞市康瑞电子有限公司 Dongguan Konnra Electronics co., LTD.	PROJECT	PART NO.	A3000N***40P60
	△				.X±0.30	X°±1°	DRAWN: 闵昕皓							
	△				.XX±0.20	.X°±	CHECKED:		VER.	SCALE:	N/A	DRAWING NO.	3000HF101-4-S	
	△	LTR	NAME	DATE	VERISION RECORD	.XXX±0.10	.XX°±	APPROVED:	A	SHEET:	1/1			
	1	2	3	4	5	6	7	8	9					