



◆ SPECIFICATIONS

- Current rating: 5A AC, DC
- Voltage rating: 250V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 1500V AC/ minute.
- Contact resistance: 10mΩ Max.

Material: Nylon66 UL94 V-0/2

Circuits: 2*2

Suitable: KR3000 series Terminal

Mates With KR3000 series dual row female housing and KR3000 series dual row wafer

PART NO. : A3000M20270P60

0:UL94V-2
1:UL94V-0



				GENERAL TOLERANCE		UNIT: mm		DATE		TITLE:				
				.X ± 0.30		X° ± 3°		DRAWN: 闵昕皓		2016.06.28		KR3000		
程如意 17.02.28 增加防火等级料号规格				.XX ± 0.20		.X° ±		CHECKED:				MX3.0双排公HOUSING		
曾广博 16.02.29 修改料号编码,整理图面				.XXX ± 0.10		.XX° ±		APPROVED:				2*2P		
王钰徽 2015.11.16 增加2X1P的B尺寸管控												VER. SCALE: 1:1		
LTR ECN NO. NAME DATE VERISION RECORD												A2 SHEET: 1/2		



东莞市康瑞电子有限公司
Dongguan Konnra Electronics co., LTD.

PROJECT PART NO. A3000M20270P6*
DRAWING NO. 3000HM203-7-S