


- ◆ SPECIFICATIONS
- Current rating: 3A AC, DC
 - Voltage rating: 250V AC,DC
 - Temperature range: -25°C ~ +85°C
 - Insulation resistance: 1000MΩ Min.
 - Withstanding voltage: 1500V AC/ minute.
 - Contact resistance: 20mΩ Max.

Material:
 Insulator: PBT UL 94V-0
 Contact: Brass
 Plating: Gold flash over Nickel
 Suitable KR2542 Series Housing

C2545VD 205 20PB 4 1
 4:盒装
 205:2*5P
 232:2*32P

Circuits	Dimension			
	A	B	C	D
2*5	31.90	21.68	10.16	17.82
2*7	36.98	26.76	15.24	22.90
2*8	39.52	29.30	17.78	25.44
2*10	44.60	34.38	22.85	30.52
2*13	52.22	42.00	30.46	38.14
2*15	57.33	47.08	35.56	43.22
2*17	62.38	52.16	40.64	48.30
2*20	70.00	59.78	48.26	55.92
2*25	82.70	72.48	60.96	68.62
2*30	95.40	85.18	73.66	82.32
2*32	100.48	90.26	78.74	86.40

△		GENERAL TOLERANCE		UNIT: mm		DATE		TITLE:	
△		.X±0.30 X°±1°		DRAWN: 闵昕皓		2017.04.10		杜邦 2.54 双排 180° 勾勾牛角 L=16.0	
△		.XX±0.20 .X°±		CHECKED:				长耳	
△		.XXX±0.10 .XX°±		APPROVED:				VER. SCALE: N/A	
LTR	NAME	DATE	VERISION RECORD					A1 SHEET: 1/1	
1	2	3	4	5	6	7	8	9	


东莞市康瑞电子有限公司
 Dongguan Konnra Electronics co., LTD.

PROJECT	PART NO.	C2545VD***20PB41
DRAWING NO.		2545WVD02-2-S