



**SPECIFICATIONS**

1. Current rating: 1A AC, DC
2. Voltage rating: 150V AC, DC
3. Temperature range: -40°C ~ +105°C
4. Insulation resistance: 500MΩ Min.
5. Withstanding voltage: 500V AC/minute.
6. Contact resistance: 30mΩ Max.

**Applicable Wires:**

AWG#28-#32

Insulation O.D.: 1.00mm MAX

Material: Phosphor Bronze

Finish: Tin or gold Plated over Nickel

Suitable KR1256 series housing

Q'ty/reel: 10,000PCS

T12560P \*\*\* 01A

T01: 镀锡

G01: 全金

G04: 全金5u"

S00: 素材

F		E		D		C		B		A	
MARK		REVISION DESCRIPTION		SIGNATURE		DATE		TOLERANCE		TITLE:	
A2		更改料号及图框格式		LJT		2020.04.01		X.X ± 0.30 X.XX ± 0.20 X.XXX ± 0.10 Angle ± 2°		DF13 Terminal	
1		2		3		4		5		6	
UNIT: mm		SCALE: N/A		SHEET: 1/1		PROJECTION		DRAWN: LiuJingtian 2020.04.01		CHECKED:	
REV: A2		DRAWING NO.: 1256T101-A-S		PART NO.: T12560P***01A		APPROVED:		KONNRA 东莞市康瑞电子有限公司		Dongguan Konnra Electronics Co., Ltd.	
8		9		E		D		C		B	