



SPECIFICATIONS

1. Current rating: 3A (AWG #24)AC, DC
2. Voltage rating: 100V AC,DC
3. Temperature range: -40°C ~ +105°C
4. Insulation resistance:500MΩ Min.
5. Withstanding voltage: 500V AC/ minute.
6. Contact resistance: 20m Ω Max.

Material: PBT UL94 V-0
 Suitable: KR1507 series terminal
 Mate with KR1507 series wafer

Ordering Code:

H15070 *** 24 01A

No.of Circuits }
 102:02,115:15 }
 Insulator Material }
 24:PBT White }

15P	26.80	21.00	23.70
14P	25.30	19.50	22.20
13P	23.80	18.00	20.70
12P	22.30	16.50	19.20
11P	20.80	15.00	17.70
10P	19.30	13.50	16.20
9P	17.80	12.00	14.70
8P	16.30	10.50	13.20
7P	14.80	9.00	11.70
6P	13.30	7.50	10.20
5P	11.80	6.00	8.70
4P	10.30	4.50	7.20
3P	8.80	3.00	5.70
2P	7.30	1.50	4.20
PIN数	A	B	C

KONNRA 东莞市康瑞电子有限公司
 Dongguan Konnra Electronics CO., LTD

PART NO. : H150701**2401A

VER. : A2 DRAWING NO. : 1507H101-A-S

DRAWN: 谭虎雄 2020.01.06

CHECKED:

APPROVED:

TITLE: MK1.5内扣 Housing

TOLERANCE
 X.X ±0.30
 X.XX ±0.20
 X.XXX ±0.10
 Angle ±3°

DATE: 2020.01.06

SIGNATURE: TLX

REVISION DESCRIPTION

更改料号及图框格式

删除尺寸

更改料号及图框格式

LTR

1 2 3 4 5 6 7 8 9