



**SPECIFICATIONS**

- 1. Current rating: 3A AC, DC
- 2. Voltage rating: 250V AC, DC
- 3. Temperature range: -40°C ~ +105°C
- 4. Insulation resistance: 1000MΩ/ min.
- 5. Withstanding voltage: 800V AC/ minute.
- 6. Contact resistance: 20mΩ/ max.

Material: PA66 UL 94V-0

Ordering Code:

H20050 \*\*\* \*\* 01A

No. of Circuits }  
 202: 2x2, 222: 2x22  
 Insulator Material }  
 01: PA66 White V0

Circuits	Dimensions			Circuits	Dimensions		
	A	B	B		A	B	C
2x2	2.00	6.00	4.40	2x13	24.00	28.00	26.40
2x3	4.00	8.00	6.40	2x14	26.00	30.00	28.40
2x4	6.00	10.00	8.40	2x15	28.00	32.00	30.40
2x5	8.00	12.00	10.40	2x16	30.00	34.00	32.40
2x6	10.00	14.00	12.40	2x17	32.00	36.00	34.40
2x7	12.00	16.00	14.40	2x18	34.00	38.00	36.40
2x8	14.00	18.00	16.40	2x19	36.00	40.00	38.40
2x9	16.00	20.00	18.40	2x20	38.00	42.00	40.40
2x10	18.00	22.00	20.40	2x21	40.00	44.00	42.40
2x11	20.00	24.00	22.40	2x22	42.00	46.00	44.40
2x12	22.00	26.00	24.40				

F	⚠				TOLERANCE	TITLE:	DRAWN:	<b>KONNRA</b> 东莞市康瑞电子有限公司 DongGuan Konnra Electronics CO., LTD PART NO.: H20050***0101A VER.: A1 DRAWING NO.: 2005H201-A-S
	⚠				X.X ±0.30	PHD2.0 Housing	CHECKED:	
	⚠	更改料号及图框格式	Arvin	2020.01.03	X.XX ±0.20		APPROVED:	
	LTR	REVISION DESCRIPTION	SIGNATURE	DATE	X.XXX ±0.10	UNIT: mm	SHEET: 1/1	
	1	2	3	4	5	6	7	8