


A-A SECTION



B-B SECTION

- ◆ SPECIFICATIONS
- Current rating: 3A AC, DC
  - Voltage rating: 250V AC, DC
  - Temperature range: -25°C ~ +85°C
  - Insulation resistance: 500MΩ Min.
  - Withstanding voltage: 1500V AC/ minute.
  - Contact resistance: 10mΩ Max.

PART NO.	WIRE RANGE	INSULATION O.D.	MATERIAL	FINISH	Q'TY/reel
B2507FT2AA100	AWG#22-#28	1.7mm(MAX)	Phosphor Bronze	TIN-PLATED	8,000pcs

F	4			GENERAL TOLERANCE	UNIT: mm	DATE	TITLE: JST SM 2.5 公 Terminal			东莞市康瑞电子有限公司 Dongguan Konnra Electronics co., LTD.					
	3			.X ± 0.30	X° ± 1°	DRAWN: 闵昕皓					2014.07.08				
	2	闵昕皓	2014.07.08	如图示修正尺寸	.XX ± 0.20	.X° ±	CHECKED:		VER.		SCALE:	N/A	PROJECTION	PART NO.	B2507FT2AA100
	1	闵昕皓	2014.06.20	如图示修正尺寸	.XXX ± 0.10	.XX° ±	APPROVED:		A		SHEET:	1/1	DRAWING NO.	2507TM01-2-S	
	LTR	NAME	DATE	VERISION RECORD											
	1	2	3	4	5	6	7	8	9						