

◆ SPECIFICATIONS

- Current rating: 3A AC, DC
- Voltage rating: 250V AC, DC
- Temperature range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Insulation resistance: 1000M Ω Min.
- Withstanding voltage: 1000V AC/ minute.
- Contact resistance: 30m Ω Max.


Material: Nylon 66 UL 94V-2


Circuits: 2~15

Suitable: 2510 series Female Housing

| PART No. | Dimension | | |
|----------------|-----------|-------|-------|
| | A | B | C |
| A2510F00219P60 | 2.50 | 5.60 | 7.10 |
| A2510F00319P60 | 5.00 | 8.10 | 9.60 |
| A2510F00419P60 | 7.50 | 10.60 | 12.10 |
| A2510F00519P60 | 10.00 | 13.10 | 14.60 |
| A2510F00619P60 | 12.50 | 15.60 | 17.10 |
| A2510F00719P60 | 15.00 | 18.10 | 19.60 |
| A2510F00819P60 | 17.50 | 20.60 | 22.10 |
| A2510F00919P60 | 20.00 | 23.10 | 24.60 |
| A2510F01019P60 | 22.50 | 25.60 | 27.10 |
| A2510F01119P60 | 25.00 | 28.10 | 29.60 |
| A2510F01219P60 | 27.50 | 30.60 | 32.10 |
| A2510F01319P60 | 30.00 | 33.10 | 34.60 |
| A2510F01419P60 | 32.50 | 35.60 | 37.10 |
| A2510F01519P60 | 35.00 | 38.10 | 39.60 |

| | | | | | | | | | |
|-----|--------------|------------------|-----------------|-------------------|---------------------------------|---------------------|--------------------|--------|-----|
| △ | | | | GENERAL TOLERANCE | UNIT: mm | DATE | TITLE: | | |
| △ | | | | .X \pm 0.30 | X $^{\circ}$ \pm 1 $^{\circ}$ | DRAWN: <i>Arwin</i> | SMH250 Crimp | | |
| △ | | | | .XX \pm 0.20 | .X $^{\circ}$ \pm | CHECKED: | Style Male Housing | | |
| △ | <i>Arwin</i> | <i>2014.8.22</i> | <i>删除尺寸7.8</i> | .XXX \pm 0.10 | .XX $^{\circ}$ \pm | APPROVED: | VER. | SCALE: | N/A |
| LTR | NAME | DATE | VERISION RECORD | | | | A | SHEET: | 1/1 |


东莞市康瑞电子有限公司
 Dongguan Konnra Electronics co., LTD.

PROJECTION:  PART NO. **A2510F***19P60**

DRAWING NO. **2510HM101-1-S**

1 2 3 4 5 6 7 8 9

A

B

C

D

E

F

A

B

C

D

E

F

1 2 3 4 5 6 7 8 9