



◆ SPECIFICATIONS

- Current rating: 3A AC, DC
- Voltage rating: 250V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 1000V AC/ minute.
- Contact resistance: 30mΩ Max.

Material: Nylon 66 UL 94V-2  
 Circuits: 2~15  
 Suitable: 2510 series Female Housing

PART No.	Dimension		
	A	B	C
A2510M00219P60	2.50	6.10	7.90
A2510M00319P60	5.00	8.60	10.40
A2510M00419P60	7.50	11.10	12.90
A2510M00519P60	10.00	13.60	15.40
A2510M00619P60	12.50	16.10	17.90
A2510M00719P60	15.00	18.60	20.40
A2510M00819P60	17.50	21.10	22.90
A2510M00919P60	20.00	23.60	25.40
A2510M01019P60	22.50	26.10	27.90
A2510M01119P60	25.00	28.60	30.40
A2510M01219P60	27.50	31.10	32.90
A2510M01319P60	30.00	33.60	35.40
A2510M01419P60	32.50	36.10	37.90
A2510M01519P60	35.00	38.60	40.40

	GENERAL TOLERANCE		UNIT: mm		DATE		TITLE: SMP250 Crimp Style Female Housing			东莞市康瑞电子有限公司 Dongguan Konnra Electronics co., LTD.
	.X±0.30	X°±1°	DRAWN:	朱佑武	2013.5.25					
	.XX±0.20	.X°±	CHECKED:			VER.    SCALE:    N/A A       SHEET:    1/1	PROJECTION	PART NO.	A2510M***19P60	
	.XXX±0.10	.XX°±	APPROVED:			DRAWING NO.    2510HF101-1-S				