

◆ SPECIFICATIONS

- Current rating: 3A AC, DC
- Voltage rating: 250V AC, DC
- Temperature range:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Insulation resistance:  $1000\text{M}\Omega$  Min.
- Withstanding voltage: 600V AC/ minute.
- Contact resistance:  $20\text{m}\Omega$  Max.

Material : Phosphor Bronze

Applicable Wires:

Conductor size: AWG#28~#22

Insulation O.D.: 1.6mm Max.

Suitable: KR2545(9) Series Housing or  
KR2541 series male housing

MOQ: 15,000PCS


B2541M T 4AA100

Plating:


B=Selective Gold Plated

G=Gold Plated


T=Tin Plated



SEC: A-A



SEC: B-B




SEC: C-C

F	△				GENERAL TOLERANCE		UNIT: mm		DATE		TITLE: MK2.54 超薄母 Terminal	
	△				$.X \pm 0.30$	$X^{\circ} \pm 1^{\circ}$	DRAWN:	Arvin	2018.01.31			
	△				$.XX \pm 0.20$	$.X^{\circ} \pm$	CHECKED:					
	△	Arvin	2018.01.31	改善端子插入力	$.XXX \pm 0.10$	$.XX^{\circ} \pm$	APPROVED:			VER.	SCALE:	N/A
	LTR	NAME	DATE	VERSION RECORD						A2	SHEET:	1/1

 东莞市康瑞电子有限公司  
Dongguan Konnra Electronics co., LTD.

PROJECT PART NO. B2541M4AA100

 DRAWING NO. 2541TF101-4-S