

◆ SPECIFICATIONS

- Current rating: 9A AC, DC (AWG#16, 2 Circuit)
- Voltage rating: 600V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 1000MΩ Min.
- Withstanding voltage: 1500V AC/ minute.
- Contact resistance: 10mΩ Max.

Material:


Insulator: Nylon 66 UL 94V-2

Contact: Brass

Plating: Tin plated over Nickel

Circuits: 2~6

Circuits	Dimensions	
	A	B
02	4.20	9.60
03	8.40	13.80
04	12.60	18.00
05	16.80	22.20
06	21.00	26.40

④				GENERAL TOLERANCE		UNIT: mm		DATE	TITLE: MX 4.2 单排 90度 WF 实心针无柱			 <b>东莞市康瑞电子有限公司</b> Dongguan Konnra Electronics co., LTD.		
③				.X ± 0.30	X° ± 1°	DRAWN:	Arvin	2018.03.30						
②				.XX ± 0.20	.X° ±	CHECKED:			VER.	SCALE:	N/A	PROJECT	PART NO.	C4200RD***69P63B
①				.XXX ± 0.10	.XX° ±	APPROVED:			A1	SHEET:	1/1	DRAWING NO.	4200WHD103-6-S	
LTR	NAME	DATE	VERISION RECORD											