



◆ SPECIFICATIONS
 Current rating: 9A(2P AWG#16) AC, DC
 Voltage rating: 600V AC, DC
 Temperature range: -25°C ~ +85°C
 Insulation resistance: 1000MΩ Min.
 Withstanding voltage: 1500V AC/ minute.
 Contact resistance: 10mΩ Max.

Material: Nylon 66 UL 94V-2
 Circuits: 2*1~2*12P
 Suitable: KR4200 series female terminal
 Mates with KR4200 series double row female housing or wafer

F	④				GENERAL TOLERANCE		UNIT: mm		DATE		TITLE: KR4200 MK 4.2 Double Row Male Housing			 东莞市康瑞电子有限公司 Dongguan Konnra Electronics co., LTD.			
	③				.X ± 0.30	X° ± 1°	DRAWN:	闵昕皓	2016.12.09								
	②	闵昕皓	2016.12.09	更正尺寸规格		.XX ± 0.20	.X° ±	CHECKED:			VER.	SCALE:	N/A	PROJECT	PART NO.	A4200F2**13P60	
	①	闵昕皓	2015.08.20	修正尺寸及视图		.XXX ± 0.10	.XX° ±	APPROVED:			A2	SHEET:	1/1	 DRAWING NO.	4200HM201-1-S		
	LTR	NAME	DATE	VERISION RECORD													
	1	2	3	4	5	6	7	8	9								