



◆ SPECIFICATIONS

- Current rating: 0.5A AC, DC
- Voltage rating: 30V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 100MΩ Min.
- Withstanding voltage: 200V AC/ minute.
- Contact resistance: 20mΩ Max.

Material:
 Insulator: Nylon 46 UL 94V-0
 Suitable: KR0803 Series Single Row Wafer

3D View

Dimensions			
Pin	A	B	C
2P	0.80	1.80	4.40
3P	1.60	2.60	5.20
4P	2.40	3.40	6.00
5P	3.20	4.20	6.80
6P	4.00	5.00	7.60
7P	4.80	5.80	8.40
8P	5.60	6.60	9.20
9P	6.40	7.40	10.00
10P	7.20	8.20	10.80
11P	8.00	9.00	11.60
12P	8.80	9.80	12.40
13P	9.60	10.60	13.20
14P	10.40	11.40	14.00
15P	11.20	12.20	14.80
16P	12.00	13.00	15.60
20P	15.20	16.20	18.80

F	△4			GENERAL TOLERANCE	UNIT: mm	DATE	TITLE: JST 0.8mm		东莞市康瑞电子有限公司 DongGuan Konnra Electronics CO.,LTD	
	△3			.X ± 0.30	X° ± 1°	DRAWN: 闵昕皓	2016.04.19			PROJECT
	△2			.XX ± 0.20	.X° ±	CHECKED:				
	△1			.XXX ± 0.10	.XX° ±	APPROVED:				A0803O0**18P40
	LTR	NAME	DATE	VERISION RECORD			VER.	SCALE:	N/A	DRAWING NO.
	1	2	3	4	5	6	A1	SHEET:	1/1	