



◆ SPECIFICATIONS

- Current rating: 1A AC, DC
- Voltage rating: 50V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 100MΩ Min.
- Withstanding voltage: 500V AC/ minute.
- Contact resistance: 20mΩ Max.

Material: PBT UL 94V-0  
 Circuits: 10, 16, 20, 30, 40, 50  
 Suitable: KR1000 series Terminal  
 Mates With KR1000 Series Dual Row Wafer

PART NO.	Dimensions		
	A	B	C
A1000O20589PB0	4.00	6.20	8.00
A1000O20889PB0	7.00	9.20	11.00
A1000O21089PB0	9.00	11.20	13.00
A1000O21589PB0	14.00	16.20	18.00
A1000O22089PB0	19.00	21.20	23.00
A1000O22589PB0	24.00	26.20	28.00

△				GENERAL TOLERANCE	UNIT: mm	DATE	TITLE:
△				.X ± 0.25	X° ± 1°	2018.01.12	JST SHR 1.00
△				.XX ± 0.15	.X° ±		双排Housing
△	Arvin	2018.01.12	增加2#SP尺寸规格	.XXX ± 0.10	.XX° ±		VER. SCALE: N/A
LTR	NAME	DATE	VERISION RECORD		APPROVED:		A2 SHEET: 1/1

东莞市康瑞电子有限公司  
 DongGuan Konnra Electronics CO.,LTD

PROJECT PART NO. A1000O2\*\*89PB0  
 DRAWING NO. 1000H201-8-S