

Recommended P.C.B. Layout
Total tolerance: ±0.05mm

Ordering code:

C1000RS *** 44 ** * 0

002: 2P
020: 20P
1: 管装
2: 卷装
P9: PA9T

◆ SPECIFICATIONS

- Current rating: 1A AC, DC
- Voltage rating: 50V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 100MΩ Min.
- Withstanding voltage: 500V AC/ minute.
- Contact resistance: 20mΩ Max.

Material:

Insulator: PA9T UL 94V-0


Contact: Copper alloy/Tin plated over Nickel

Fitting Nail: Copper alloy/Tin plated over Nickel

Circuits: 2~20

Mates With KR1000 Series Single Row Housing

PIN NO.	DIMENSIONS		PIN NO.	DIMENSIONS	
	A	B		A	B
02P	1.00	4.00	12P	11.00	14.00
03P	2.00	5.00	13P	12.00	15.00
04P	3.00	6.00	14P	13.00	16.00
05P	4.00	7.00	15P	14.00	17.00
06P	5.00	8.00	16P	15.00	18.00
07P	6.00	9.00	17P	16.00	19.00
08P	7.00	10.00	18P	17.00	20.00
09P	8.00	11.00	19P	18.00	21.00
10P	9.00	12.00	20P	19.00	22.00
11P	10.00	13.00			

4				GENERAL TOLERANCE	UNIT: mm	DATE	TITLE:	 东莞市康瑞电子有限公司 DongGuan Konnra Electronics CO.,LTD		
3				.X ± 0.25	X° ± 1°	DRAWN: 闵昕皓	2016.12.21			
2				.XX ± 0.15	.X° ±	CHECKED:		PROJECT		
1	闵昕皓	2016.12.21	修正 P.C Board Layout	.XXX ± 0.10	.XX° ±	APPROVED:		PART NO. C1000RS***44***0		
LTR	NAME	DATE	VERISION RECORD					DRAWING NO. 1000WHS101-4-S		
1	2	3	4	5	6	7	8	9		