

◆ SPECIFICATIONS

- Current rating: 1A AC, DC
- Voltage rating: 50V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 100MΩ Min.
- Withstanding voltage: 500V AC/ minute.
- Contact resistance: 20mΩ Max.

Material: PBT UL 94V-0
 Circuits: 2~20
 Suitable: KR1000 series Terminal
 Mates With KR1000 Series Single Row Wafer


Ordering code:

A1000O***79**0
 PIN数 ————
 G: 无卤
 PB: PBT
 P6: PA66

PART NO.	Dimensions	
	A	B
A1000O00279PB0	1.00	3.00
A1000O00379PB0	2.00	4.00
A1000O00479PB0	3.00	5.00
A1000O00579PB0	4.00	6.00
A1000O00679PB0	5.00	7.00
A1000O00779PB0	6.00	8.00
A1000O00879PB0	7.00	9.00
A1000O00979PB0	8.00	10.00
A1000O01079PB0	9.00	11.00
A1000O11279PB0	10.00	12.00
A1000O01279PB0	11.00	13.00
A1000O01379PB0	12.00	14.00
A1000O01479PB0	13.00	15.00
A1000O01579PB0	14.00	16.00
A1000O01679PB0	15.00	17.00
A1000O01779PB0	16.00	18.00
A1000O01879PB0	17.00	19.00
A1000O01979PB0	18.00	20.00
A1000O02079PB0	19.00	21.00

F	△			GENERAL TOLERANCE		UNIT: mm		DATE		TITLE:	
	△			.X ± 0.25	X° ± 1°	DRAWN:	朱佑武	2013.1.2	JST SH 1.0 Housing		
	△			.XX ± 0.15	.X° ±	CHECKED:			无耳		
	△			.XXX ± 0.10	.XX° ±	APPROVED:			VER.	SCALE:	N/A
LTR	NAME	DATE	VERISION RECORD						A	SHEET:	1/1

 东莞市康瑞电子有限公司
 DongGuan Konnra Electronics CO.,LTD

PROJECT	PART NO.	A1000O***79**0
	DRAWING NO.	1000H102-7-S