



- ◆ SPECIFICATIONS
- Current rating: 1A AC, DC
 - Voltage rating: 50V AC, DC
 - Temperature range: -25°C ~ +85°C
 - Insulation resistance: 100MΩ Min.
 - Withstanding voltage: 500V AC/ minute.
 - Contact resistance: 20mΩ Max.

Material: Phosphor Bronze
 Finish: Plated Tin over Nickel
 Applicable wires: AWG #28~#32
 Insulation O.D 0.4 to 0.8mm
 Suitable: KR1000 series Housing
 Qty/reel: 20,000PCS



F	△4			GENERAL TOLERANCE		UNIT: mm		DATE		TITLE: JST SH 1.0 Crimp Terminal			东莞市康瑞电子有限公司 DongGuan Konnra Electronics CO.,LTD					
	△3			.X±0.3	X°±1°	DRAWN:	朱佑武	2013.4.2										
	△2			.XX±0.2	.X°±	CHECKED:			VER.	SCALE:	1:1	PROJECT	PART NO.	B1000*5AA100				
	△1			.XXX±0.1	.XX°±	APPROVED:	周志龙	2013.4.2	A1	SHEET:	1/1	DRAWING NO.		1000T01-5-S				
	LTR	NAME	DATE	VERISION RECORD														
	1			2		3		4		5		6		7		8		9