



- ◆ SPECIFICATIONS
- Current rating: 1A AC, DC
  - Voltage rating: 50V AC, DC
  - Temperature range: -25°C ~ +85°C
  - Insulation resistance: 100MΩ Min.
  - Withstanding voltage: 500V AC/ minute.
  - Contact resistance: 20mΩ Max.

B1004O\*2AA100

T:镀锡  
G:镀全金  
B:镀半金



SECTION A-A



SECTION B-B

Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
B1004O*2AA100	AWG#28-#34	0.80mm(max)	Phosphor Bronze	Gold-Plated	15,000PCS

④				GENERAL TOLERANCE		UNIT: mm		DATE		TITLE: JST1.0mm超薄 双排 Terminal		
③				.X±0.25	X°±1°	DRAWN:	朱佑武	2011.5.24				
②				.XX±0.15	.X°±	CHECKED:						
①				.XXX±0.08	.XX°±	APPROVED:	周志龙	2011.5.24				
LTR	NAME	DATE	VERISION RECORD						VER.	SCALE:	N/A	
									A	SHEET:	1/1	


**东莞市康瑞电子有限公司**  
 Dongguan Konrra Electronics co., LTD.

PROJECTION	PART NO.	B1004O*2AA100
DRAWING NO.		1004T01-2-S

1 2 3 4 5 6 7 8 9

A

B

C

D

E

F

A

B

C

D

E

F

1 2 3 4 5 6 7 8 9