




- ◆ SPECIFICATIONS
- Current rating: 1A AC, DC
 - Voltage rating: 50V AC, DC
 - Temperature range: -25°C ~ +85°C
 - Insulation resistance: 100MΩ Min.
 - Withstanding voltage: 500V AC/ minute.
 - Contact resistance: 20mΩ Max.

B1005O*1AA100

T: 镀锡
G: 镀全金
B: 镀半金



SECTION A-A



SECTION B-B

Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
B1005O*1AA100	AWG#28-#32	0.80mm(max)	Phosphor Bronze	Tin/Gold-Plated	20,000PCS

F	△		GENERAL TOLERANCE		UNIT: mm		DATE		TITLE: JST1.0mm超薄 单 排Terminal			东莞市康瑞电子有限公司 Dongguan Konra Electronics co., LTD.	
	△		.X±0.25	X°±1°	DRAWN: 朱信武		2011.5.24						
	△		.XX±0.15		.X°±	CHECKED:				PROJECTION		PART NO. B1005O*1AA100	
	△		.XXX±0.08		.XX°±	APPROVED: 周志龙		2011.5.24		VER. A		SCALE: N/A	
LTR		NAME		DATE		VERISION RECORD				SHEET: 1/1		DRAWING NO. 1005T01-1-S	
1		2		3		4		5		6		7	
8		9											