



Recommended P.C.B Layout  
General Tolerance±0.05

◆SPECIFICATIONS

Current rating: 1A AC, DC  
Voltage rating: 125V AC,DC  
Temperature range: -25°C ~ +85°C  
Insulation resistance: 100MΩ Min.  
Withstanding voltage: 500V AC/ minute.  
Contact resistance: 20m Ω Max.

Material:

Insulator: PA9T UL 94V-0  
Contact: Phorphos Bronze  
Solder Nail: Phorphos Bronze  
Plating: MatteTin plated over Nickel  
Circuits: 2~20  
Suitable: KR1005 series Housing  
Mates With KR1005 Series Terminal

Poles	Dimensions (mm)		
	A	B	C
02	1.00	3.90	2.50
03	2.00	4.90	3.50
04	3.00	5.90	4.50
05	4.00	6.90	5.50
06	5.00	7.90	6.50
07	6.00	8.90	7.50
08	7.00	9.90	8.50
09	8.00	10.90	9.50
10	9.00	11.90	10.50
11	10.00	12.90	11.50
12	11.00	13.90	12.50
13	12.00	14.90	13.50
14	13.00	15.90	14.50
15	14.00	16.90	15.50
16	15.00	17.90	16.50
17	16.00	18.90	17.50
18	17.00	19.90	18.50
19	18.00	20.90	19.50
20	19.00	21.90	20.50

Ordering Code:

C1005RS \*\*\* 14P9 \* 0  
① ②

① NO.of Circuit: (002~020)

② Packing Type:  
2=Reel&Tape

F	④				GENERAL TOLERANCE		UNIT: mm		DATE		TITLE:				
	③				.X±0.30	X°±1°	DRAWN:	闵昕皓	2015.10.10	JST1.0 超薄 带扣SMT 90° Wafer					
	②				.XX±0.20	.X°±	CHECKED:			VER.	SCALE:	N/A	PROJECT	PART NO.	C1005RS***14***0
	①				.XXX±0.10	.XX°±	APPROVED:			A1	SHEET:	1/1			
LTR	NAME	DATE	VERISION RECORD	1	2	3	4	5	6	7	8	9			



东莞市康瑞电子有限公司  
Dongguan Konnra Electronics co., LTD.