




- ◆ SPECIFICATIONS
- Current rating: 1A AC, DC
 - Voltage rating: 50V AC, DC
 - Temperature range: -25°C ~ +85°C
 - Insulation resistance: 100MΩ Min.
 - Withstanding voltage: 500V AC/ minute.
 - Contact resistance: 20mΩ Max.

B1005O*1AA100

T: 镀锡
G: 镀全金
B: 镀半金



SECTION A-A




SECTION B-B

Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
B1005O*1AA100	AWG#28-#32	0.80mm(max)	Phosphor Bronze	Tin/Gold-Plated	20,000PCS

△				GENERAL TOLERANCE	UNIT: mm	DATE	TITLE: JST1.0mm超薄 单 排Terminal
△				.X±0.25	X° ±1°	DRAWN: 朱信武 2011.5.24	
△				.XX±0.15	.X° ±	CHECKED:	
△				.XXX±0.08	.XX° ±	APPROVED: 周志龙 2011.5.24	
LTR	NAME	DATE	VERSION RECORD				VER. SCALE: N/A A SHEET: 1/1

 东莞市康瑞电子有限公司
Dongguan Konra Electronics co., LTD.

PROJECTION PART NO. B1005O*1AA100

 DRAWING NO. 1005T01-1-S