



SECTION A-A



SECTION B-B



SECTION C-C

◆ SPECIFICATIONS

- Current rating: 1A AC, DC
- Voltage rating: 125V AC, DC
- Temperature range: -25°C ~ +85°C
- Insulation resistance: 100MΩ Min.
- Withstanding voltage: 250V AC/ minute.
- Contact resistance: 20mΩ Max.

Material: Phosphor Bronze
Plating: Tin plated over Nickel

Applicable wire:
AWG#28~#32

Insulation O.D. 1.00mm Max.
Suitable: KR1251 series Housing
Q'ty: 20,000PCS/Reel

F	△4			GENERAL TOLERANCE		UNIT: mm	DATE	TITLE:		 东莞市康瑞电子有限公司 DongGuan Konnra Electronics CO.,LTD	
	△3			.X±0.30	X°±1°	DRAWN: 闵昕皓	2017.07.19	MX1.25 空接 Terminal			
	△2			.XX±0.20	.X°±	CHECKED:		VER.	SCALE:		N/A
	△1			.XXX±0.10	.XX°±	APPROVED:		A1	SHEET:		1/1
LTR	NAME	DATE	VERISION RECORD					PROJECTION	PART NO.	B1251FT2AA100	
									DRAWING NO.	1251T01-2-S	

1

2

3

4

5

6

7

8

9