



- ◆SPECIFICATIONS
- Current rating: 3A AC, DC
 - Voltage rating: 250V AC,DC
 - Temperature range: -25°C ~ +85°C
 - Insulation resistance: 1000MΩ Min.
 - Withstanding voltage: 800V AC/ minute.
 - Contact resistance: 20m Ω Max.

Material:
 Insulator: Nylon 66 UL 94V-0
 Contact: Brass
 Plating: Tin plated over Nickel

Part No.	Dimension mm	
	A	B
C2543VD00219P630	2.54	5.08
C2543VD00319P630	5.08	7.62
C2543VD00419P630	7.62	10.16
C2543VD00519P630	10.16	12.70
C2543VD00619P630	12.70	15.24
C2543VD00719P630	15.24	17.78
C2543VD00819P630	17.78	20.32
C2543VD00919P630	20.32	22.86
C2543VD01019P630	22.86	25.40
C2543VD01119P630	25.40	27.94
C2543VD01219P630	27.94	30.48
C2543VD01319P630	30.48	33.02
C2543VD01419P630	33.02	35.56
C2543VD01519P630	35.56	38.10
C2543VD01619P630	38.10	40.64

△				GENERAL TOLERANCE		UNIT: mm	DATE	TITLE: AMP 2.54 180° Wafer		
△				.X±0.30	X°±1°	DRAWN: 朱佑武	2012.10.18			
△				.XX±0.20	.X°±	CHECKED:		VER.	SCALE:	N/A
△				.XXX±0.10	.XX°±	APPROVED:		A	SHEET:	1/1
LTR	NAME	DATE	VERISION RECORD							
1	2	3	4	5	6	7	8	9		


东莞市康瑞电子有限公司
 Dongguan Konnra Electronics co., LTD.

PROJECTION:  PART NO. C2543VD***19P630
 DRAWING NO. 2543WVD01-1-S