




- ◆ SPECIFICATIONS
- Current rating: 5A AC, DC
  - Voltage rating: 250V AC, DC
  - Temperature range: -25°C ~ +85°C
  - Insulation resistance: 1000MΩ Min.
  - Withstanding voltage: 1500V AC/ minute.
  - Contact resistance: 10mΩ Max.

Material: Phosphor Bronze  
 Finish: Tin plated over Nickel  
 Applicable wires: AWG #20~#24  
 Insulation O.D 1.30~1.80 mm  
 Suitable: KR3000 series Housing  
 Qty/reel: 10,000PCS

B3000F\*4AA\*00

- T: 镀锡
  - B: 半金
  - G: 全金
  - L: 素材
- 1: 先冲后镀  
 3: 素材



A-A SECTION

B-B SECTION

<table border="1"> <tr> <td>4</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>程如意</td> <td>16.06.27 更新图面</td> </tr> <tr> <td>2</td> <td>王钰微</td> <td>2015.05.29 改善端子与塑胶配合, 尺寸由1.40改为1.12</td> </tr> <tr> <td>1</td> <td>龙一蛟</td> <td>2014.11.14 新增规格</td> </tr> <tr> <td>LTR</td> <td>NAME</td> <td>DATE</td> </tr> <tr> <td>1</td> <td>2</td> <td>3</td> </tr> </table>			4			3	程如意	16.06.27 更新图面	2	王钰微	2015.05.29 改善端子与塑胶配合, 尺寸由1.40改为1.12	1	龙一蛟	2014.11.14 新增规格	LTR	NAME	DATE	1	2	3	GENERAL TOLERANCE .X ± 0.30 X° ± 1° .XX ± 0.20 .X° ± .XXX ± 0.10 .XX° ±		UNIT: mm DATE 2016.06.27		TITLE: Molex 3.0 母 Terminal			东莞市康瑞电子有限公司 Dongguan Konnra Electronics co., LTD.		
4																														
3	程如意	16.06.27 更新图面																												
2	王钰微	2015.05.29 改善端子与塑胶配合, 尺寸由1.40改为1.12																												
1	龙一蛟	2014.11.14 新增规格																												
LTR	NAME	DATE																												
1	2	3																												
VERISION RECORD 1 2 3			DRAWN: 程如意 CHECKED:		VER. SCALE: N/A B SHEET: 1/1			PROJECT PART NO. B3000F*4AA*00 DRAWING NO. 3000TF01-4-S																						
1	2	3	4	5	6	7	8	9																						