

Recommended P.C.Board Layout

◆ SPECIFICATIONS

Current rating: 3A AC, DC
 Voltage rating: 250V AC,DC
 Temperature range: -25°C ~ +85°C
 Insulation resistance: 1000MΩ Min.
 Withstanding voltage: 600V AC/ minute.
 Contact resistance: 20m Ω Max.

Material:

△ Insulator: PA9T UL 94V-0

Contact: Brass

Plating: Gold flash plated over Nickel

Circuits: 2~12

C2541RS *** 10P9 * A

002:2P

1:管装

012:12P


2:卷装

PART No.	Dimension	
	A	B△
C2541RS00210P9*A	2.54	8.89
C2541RS00310P9*A	5.08	11.43
C2541RS00410P9*A	7.62	13.97
C2541RS00510P9*A	10.16	16.51
C2541RS00610P9*A	12.70	19.05
C2541RS00710P9*A	15.24	21.59
C2541RS00810P9*A	17.78	24.13
C2541RS00910P9*A	20.32	26.67
C2541RS01010P9*A	22.86	29.21
C2541RS01110P9*A	25.40	31.75
C2541RS01210P9*A	27.94	34.29

△				GENERAL TOLERANCE		UNIT: mm		DATE		TITLE:	
△				. X ± 0.30	X° ± 1°	DRAWN: 闵昕皓		2017.08.16		MX 2.54 SMT 90° 超薄Wafer带三角柱	
△				. XX ± 0.20	. X° ±	CHECKED:				VER. SCALE: N/A	
△	闵昕皓	2017.08.16	依实物修正视图和尺寸		. XXX ± 0.10	. XX° ±	APPROVED:				A1 SHEET: 1/1
LTR	NAME	DATE	VERISION RECORD								PROJECT PART NO. C2541RS***10P9*A



东莞市康瑞电子有限公司
 Dongguan Konnra Electronics co., LTD.



DRAWING NO. 2541WHS03-1-S