

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.2kgf(MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
UL 94V-0 PBT White/Black
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
2. 外壳: Shell:
Nickel Plating

F	④			GENERAL TOLERANCE		UNIT: mm		DATE	TITLE:		
	③			.X ± 0.35	X° ± 1°	DRAWN:	程如意	2012.5.9	USB 单层90度加后盖母座 (外扣直角型)		
	②			.XX ± 0.25	.X° ±	CHECKED:			VER.	SCALE:	N/A
	①			.XXX ± 0.10	.XX° ±	APPROVED:			A1	SHEET:	1/1
	LTR	NAME	DATE	VERISION RECORD						DRAWING NO.	




东莞市康瑞电子有限公司
DongGuan Konnra Electronics CO., LTD

PROJECT

PART NO.

U02S001111A



DRAWING NO.