

基本外形尺寸 (mm)					载荷 (kN)		极限转速 (rpm)		轴承型号	相关安装尺寸 (mm)			质量 (kg)
d	D	B	r <sub>1, min</sub>	r <sub>3, min</sub>	C <sub>r</sub>	C <sub>or</sub>	脂润滑	油润滑		d <sub>a, min</sub>	D <sub>a, max</sub>	r <sub>a, max</sub>	参考
							Grease	Oil					Refer.
100	140	24	1.1	1	132	224	1000	2200	NCF2920V	106.5	133.5	1	1.15
100	150	37	1.5	1	242	375	950	2000	NCF3020V	108	142	1.5	2.2
100	180	46	2.1	2.1	380	530	850	1800	NCF2220V	111	169	2	5.1
100	215	73	3	-	704	900	600	1200	NJG2320VH	113	202	2.5	13
110	150	24	1.1	1	140	250	900	1900	NCF2922V	116.5	143.5	1	1.25
110	170	45	2	1	330	500	850	1800	NCF3022V	119	161	2	3.65
110	200	53	2.1	2.1	440	600	750	1600	NCF2222V	122	188	2	7.15
110	240	80	3	-	858	1060	560	1100	NJG2322VH	123	227	2.5	17.5
120	165	27	1.1	1	172	290	850	1800	NCF2924V	126.5	158.5	1	1.7
120	180	46	2	1	341	550	800	1700	NCF3024V	129	171	2	3.95
120	215	58	2.1	2.1	512	735	700	1500	NCF2224V	132	203	2	9.05
120	260	86	3	-	935	1200	530	1000	NJG2324VH	133	247	2.5	22.5
130	180	30	1.5	1.1	205	360	750	1600	NCF2926V	138	172	1.5	2.3
130	200	52	2	1	429	695	700	1500	NCF3026V	139	191	2	5.8
130	230	64	3	3	605	880	670	1400	NCF2226V	143	217	2.5	11
130	280	93	4	-	1080	1430	500	950	NJG2326VH	146	264	3	28
140	190	30	1.5	1.1	220	390	700	1500	NCF2928V	148	182	1.5	2.4
140	210	53	2	1	468	750	670	1400	NCF3028V	149	201	2	6.1
140	250	68	3	3	693	1020	630	1300	NCF2228V	153	237	2.5	14.5
140	300	102	4	-	1230	1660	450	850	NJG2328VH	156	284	3	35.5
150	190	20	1.1	1	108	200	700	1500	NCF1830V	157.5	182.5	1	1.3
150	190	24	1.1	1	145	285	700	1500	NCF2830V	157.5	182.5	1	1.7
150	210	36	2	1.1	286	500	670	1400	NCF2930V	159	201	2	3.85
150	225	56	2.1	1.1	539	865	630	1300	NCF3030V	161	214	2	7.5
150	270	73	3	3	792	1180	600	1200	NCF2230V	163	257	2.5	18.5
150	320	108	4	-	1450	1930	430	800	NJG2330VH	166	177	3	42.5
150	200	20	1.1	1	112	212	670	1400	NCF1832V	167.5	192.5	1	1.45
160	200	24	1.1	1	147	305	670	1400	NCF2832V	167.5	192.5	1	1.65
160	220	36	2	1.1	297	540	630	1300	NCF2932V	169	211	2	4.05
160	240	60	2.1	1.1	583	950	600	1200	NCF3032V	171	229	2	9.1
160	290	80	3	3	990	1500	560	1100	NCF2232V	173	277	2.5	23
170	215	22	1.5	1.5	149	272	629	1300	NCF1834V	182	204	1.5	1.8
170	215	27	1.1	1	194	380	630	1300	NCF2834V	177.5	207.5	1	2.3
170	230	36	2	1.1	308	570	600	1200	NCF2934V	179	221	2	4.25
170	260	67	2.1	1.1	737	1180	560	1100	NCF3034V	181	249	2	12.5
170	310	86	4	4	1100	1700	530	1000	NCF2234V	186	294	3	28.5
170	360	120	4	-	1760	2450	380	700	NJG2334VH	186	344	3	59.5
180	225	22	1.1	1	147	275	600	1200	NCF1836V	187.5	217.5	1	1.95
180	225	27	1.1	1	201	405	600	1200	NCF2836V	187.5	217.5	1	2.6
180	250	42	2	1.1	391	695	560	1100	NCF2936V	189	241	2	6.25
180	280	74	2.1	2.1	825	1370	560	1100	NCF3036V	191	269	2	16.5
180	320	86	4	4	1120	1760	500	950	NCF2236V	196	304	3	29.5
180	380	126	4	-	1870	2650	360	670	NJG2336VH	196	364	3	69.5
190	240	24	1.5	1.1	172	320	560	1100	NCF1838V	198	232	1.5	2.45
190	240	30	1.5	1.1	229	465	560	1100	NCF2838V	198	232	1.5	3.1
190	260	42	2	1.1	440	780	560	1100	NCF2938V	199	251	2	6.55
190	290	75	2.1	2.1	858	1430	530	1000	NCF3038V	201	279	2	17
190	340	92	4	4	1230	1960	480	900	NCF2238V	206	324	3	36
200	250	24	1.5	1.1	176	335	560	1100	NCF1840V	208	242	1.5	3.4
200	250	30	1.5	1.1	233	480	560	1100	NCF2840V	208	242	1.5	2.6
200	280	48	2.1	1.5	528	965	530	1000	NCF2940V	211	269	2	9.15
200	310	82	2.1	2.1	990	1700	500	950	NCF3040V	211	299	2	22.5
200	360	98	4	4	1400	2240	450	850	NCF2240V	216	344	3	43.5
200	420	138	5	-	2290	3200	320	600	NJG2340VH	220	400	4	92
220	270	24	1.5	1.1	183	365	530	1000	NCF1844V	228	262	1.5	2.85
220	270	30	1.5	1.1	242	530	530	1000	NCF2844V	228	262	1.5	3.9
220	300	48	2.1	1.5	512	1000	480	900	NCF2944V	231	289	2	9.9
220	340	90	3	3	1190	2040	450	850	NCF3044V	233	327	2.5	29.5
240	300	28	2	1.1	260	510	480	900	NCF1848V	249	291	2	4.4
240	300	36	2	1.1	341	720	480	900	NCF2848V	249	291	2	5.7
240	320	48	2.1	1.5	583	1140	450	850	NCF2948V	251	309	2	11
240	360	92	3	3	1250	2240	430	800	NCF3048V	253	347	2.5	32
240	500	155	5	5	3140	4400	240	480	NJG2348VH	260	480	4	147
260	320	28	2	1.1	270	550	430	800	NCF1852V	269	311	2	4.75
260	320	36	2	1.1	352	780	430	800	NCF2852V	269	311	2	6.2
260	360	60	2.1	1.5	737	1430	400	750	NCF2952V	271	349	2	18.5
260	400	104	4	4	1610	2850	380	700	NCF3052V	276	384	3	46.5
260	540	165	6	-	3580	5000	200	430	NJG2352VH	286	514	5	177
260	540	206	6	6	4290	6300	150	320	NCF3352V	286	514	5	220

280	350	33	2	1.1	330	655	400	750	NCF1856V	289	341	2	7.1
280	350	42	2	1.1	446	1000	400	750	NCF2856V	289	341	2	9
280	380	60	2.1	1.5	897	1730	380	700	NCF2956V	291	369	2	20
280	420	106	4	4	1680	3050	360	670	NCF3056V	296	404	3	50
300	380	38	2.1	1.5	418	850	360	670	NCF1860V	311	369	2	10
300	380	48	2.1	1.5	572	1250	360	670	NCF2860V	311	369	2	12
300	420	72	3	3	1120	2200	340	630	NCF2960V	313	407	2.5	31.5
300	460	118	4	4	2090	3750	320	600	NCF3060V	316	444	3	69
320	400	38	2.1	1.5	440	900	340	630	NCF1864V	331	389	2	10.5
320	400	48	2.1	1.5	583	1320	340	630	NCF2864V	331	389	2	13.5
320	440	72	3	3	1140	2360	320	600	NCF2964V	333	427	2.5	33
320	480	121	4	4	2120	3900	300	560	NCF3064V	336	464	3	74.5
340	420	38	2.1	2.1	475	985	300	560	NCF1868V	359	402	2	10.7
340	460	72	3	3	1190	2500	300	560	NCF2968V	353	447	2.5	35
340	520	133	5	5	2240	4250	280	530	NCF3068V	360	500	4	100
360	440	38	2.1	1.5	457	1000	300	560	NCF1872V	371	429	2	12
360	440	48	2.1	1.5	627	1460	300	560	NCF2872V	371	429	2	15
360	480	72	3	3	1230	2600	280	530	NCF2972V	373	467	2.5	36.5
360	540	134	5	5	2640	4900	260	500	NCF3072V	380	520	4	105
380	480	46	2.1	1.5	627	1290	280	530	NCF1876V	391	469	2	19.5
380	480	60	2.1	1.5	897	2080	280	530	NCF2876V	391	469	2	25
380	520	82	4	4	1570	3250	260	500	NCF2976V	396	504	3	52.5
380	560	135	5	5	2700	5100	240	480	NCF3076V	400	540	4	110
400	500	46	2.1	1.5	627	1340	260	500	NCF1880V	411	489	2	20.5
400	500	60	2.1	1.5	913	2160	260	500	NCF2880V	411	489	2	26.5
400	540	82	4	4	1650	3450	240	480	NCF2980V	416	524	3	54.5
400	600	148	5	5	3190	6100	220	450	NCF3080V	420	580	4	145
420	520	46	2.1	1.5	660	1430	240	480	NCF1884V	431	509	2	21
420	520	60	2.1	1.5	952	2280	240	480	NCF2884V	431	509	2	28
420	560	82	4	4	1650	3600	220	450	NCF2984V	436	544	3	57
420	620	150	5	5	3300	6300	200	430	NCF3084V	440	600	4	150
440	540	46	2.1	1.5	671	1460	220	450	NCF1888V	451	529	2	22
440	540	60	2.1	1.5	968	2360	220	450	NCF2888V	451	529	2	29
440	600	95	4	4	2010	4400	200	430	NCF2988V	456	584	3	80.5
440	650	157	6	6	3740	7350	190	400	NCF3088V	466	624	5	175
460	580	56	3	3	913	1960	200	430	NCF1892V	473	567	2.5	34
460	580	72	3	3	1300	3050	200	430	NCF2892V	473	567	2.5	44
460	620	95	4	4	2050	4500	190	400	NCF2992V	476	604	3	83.5
460	680	163	6	6	4130	8000	180	380	NCF3092V	486	654	5	195
480	600	56	3	3	935	2040	190	400	NCF1896V	493	587	2.5	35.5
480	600	72	3	3	1320	3150	190	400	NCF2896V	493	587	2.5	46
480	650	100	5	5	2290	5100	180	380	NCF2996V	500	630	4	98
480	700	165	6	6	4180	8300	170	360	NCF3096V	506	674	5	205
500	620	56	3	3	952	2120	180	380	NCF18/500V	513	607	2.5	35.5
500	620	72	3	3	1340	3350	180	380	NCF28/500V	513	607	2.5	48
500	670	100	5	5	2380	5300	170	360	NCF29/500V	520	650	4	100
500	720	167	6	6	4290	8650	170	360	NCF30/500V	526	694	5	215
530	650	56	3	3	990	2240	170	360	NCF18/530V	543	637	2.5	37.5
530	650	72	3	3	1400	3450	170	360	NCF28/530V	543	637	2.5	49.5
530	710	106	5	5	2700	6000	160	340	NCF29/530V	550	690	4	120
530	780	185	6	6	5230	10600	150	320	NCF30/530V	556	754	5	300
560	680	56	3	3	1020	2360	160	340	NCF18/560V	573	667	2.5	40.5
560	680	72	3	3	1420	3650	160	340	NCF28/560V	573	667	2.5	54
560	750	112	5	5	3030	6700	150	320	NCF29/560V	580	730	4	140
560	820	195	6	6	5830	11800	140	300	NCF30/560V	586	794	5	345
600	730	60	3	3	1050	2550	150	320	NCF18/600V	613	717	2.5	49.5
600	730	78	3	3	1570	4300	150	320	NCF28/600V	613	717	2.5	67.5
600	800	118	5	5	3360	7500	140	300	NCF29/600V	620	780	4	170
630	780	69	4	4	1250	2900	140	300	NCF18/630V	646	764	3	70
630	780	88	4	4	1870	5000	140	300	NCF28/630V	646	764	3	92.5
630	850	128	6	6	3740	8650	130	280	NCF29/630V	656	824	5	205
670	820	69	4	4	1300	3150	130	280	NCF18/670V	686	804	3	74
670	820	88	4	4	1940	5300	130	280	NCF28/670V	686	804	3	97.5
670	900	136	6	6	3800	8650	120	260	NCF29/670V	696	874	5	245
710	870	74	4	4	1540	3750	120	260	NCF18/710V	726	854	3	90
710	870	95	4	4	2330	6300	120	260	NCF28/710V	726	854	3	115
710	950	140	6	6	3910	9150	110	240	NCF29/710V	736	924	5	275
750	920	78	5	5	1760	4300	110	240	NCF18/750V	770	900	4	110
750	920	100	5	5	2510	6800	110	240	NCF28/750V	770	900	4	140
750	1000	145	6	6	4460	10600	100	220	NCF29/750V	796	974	5	315
800	980	82	5	5	1940	4800	100	220	NCF18/800V	820	960	4	130
800	980	106	5	5	2750	7500	100	220	NCF28/800V	820	960	4	165
800	1060	150	6	6	4950	12200	95	200	NCF29/800V	836	1034	5	360

850	1030	82	5	5	2050	5200	95	200	NCF18/850V	870	1010	4	135
850	1030	106	5	5	2860	8000	95	200	NCF28/850V	870	1010	4	175
850	1120	155	6	6	5280	12900	90	190	NCF29/850V	886	1084	5	405
900	1090	85	5	5	2240	5700	90	190	NCF18/900V	920	1070	4	160
900	1090	112	5	5	3190	9150	90	190	NCF28/900V	920	1070	4	208
900	1180	165	6	6	5940	14600	80	170	NCF29/900V	936	1154	5	472
950	1150	90	5	5	2420	6300	80	170	NCF18/950V	970	1130	4	185
950	1150	118	5	5	3410	9800	80	170	NCF28/950V	970	1130	4	240
950	1250	175	7.5	7.5	6660	16300	75	160	NCF29/950V	983	1217	6	565
1000	1220	100	6	6	2920	7500	75	160	NCF18/1000V	1026	1194	5	230
1000	1220	128	6	6	4130	11600	75	160	NCF28/1000V	1026	1194	5	310
1000	1320	185	7.5	7.5	7480	18600	70	150	NCF29/1000V	1033	1287	6	680

